POWERED OPENING SOLENOID CONTROLLED VALVE

with Active Double Chamber

Model 710-B

Double chambered, hydraulically operated, solenoid controlled valve that either opens fully, regardless of valve differential pressure, or shuts off in response to electric signal. This valve is especially useful in very low pressure applications and in corrosive fluid systems that are controlled by external fresh water or compressed air. Normally open (NO), normally closed (NC) or LATCH models are available.

The BERMAD 700 SIGMA EN/ES series valves are hydraulic globe valves with a raised seat and double chamber actuator. They provide unobstructed flow, effective high-pressure modulation, and minimal cavitation, complying with various potable water standards.




Features & Benefits

- Certified to functional and drinking water standards: EN-1074, NSF-ANSI 61-372, WRAS, AS 5081 and others
- Designed to - Stand up to the toughest conditions
  - Excellent anti-cavitation properties
  - Wide flow range
  - High stability and accuracy
  - Drip tight sealing
- Double chamber design
  - Moderated valve reaction
  - Protected diaphragm
  - Optional operation in very low pressure
  - Moderated closing curve
- Flexible design - Easy addition of features
- Obstacle free flow pass
- V-Port throttling plug (optional) - Very stable at low flow
- High quality materials
- In-line serviceable - Easy maintenance


Typical Applications


- On/Off operation in near-zero pressure
- Water reservoirs - Bypass for direct supply during reservoir maintenance
- Filtration system - Channeling flow during backflushing in an automatic filtration system

Typical Installation




All images in this catalog are for illustration only





Closed



Open

This drawing refers to 1½ – 8"; 40-200 mm sized valves only. For other sizes please refer to the Model's IOM.

Main Valve

Size Range:
EN Series: 1½"-16"; DN40-400
ES Series: 2½"-24"; DN65-600
Pattern: "Y" (globe)
Pressure Rating: 16 bar; 25 bar
End Connection: Flanged
Plug Types: Flat disc, V-port, Cavitation cage
Temperature Rating: 80°C
For 60–80°C consult factory

Standard Materials:

Body & Cover: Ductile Iron
Bolts, Nuts & Studs: Stainless Steel
Internals: Stainless Steel, Tin Bronze, Coated Steel & POM
Diaphragm: Fabric-reinforced synthetic rubber
Seals: Synthetic rubber
Coating: Dark blue Fusion bonded epoxy
For other materials contact BERMAD

Control System

Standard Materials:

Accessories: Stainless Steel, Bronze & Brass
Tubing: Stainless Steel or Copper
Fittings: Stainless Steel or Brass

Solenoid standard materials:

Body: Brass or Stainless Steel
Elastomers: NBR or FPM
Enclosure: Molded Epoxy

Solenoid Electrical Data:

Voltages:
(AC): 24, 110-120, 220-240, (50-60Hz)
(DC): 12, 24, 110, 220
Power Consumption:
(AC): 30VA, inrush; 15VA (8W), holding or 70VA, inrush; 40VA (17.1W), holding
(DC): 8-11.6W
Values may vary according to specific solenoid model. For more details check solenoid product page.

Notes

- Inlet Pressure, Outlet Pressure and Flow-rate are required for optimal sizing.
- Recommended maximum flow velocity: 6.0 m/sec; 20 ft/sec.
- Minimum operating pressure: 0.2 bar; 3 psi. External operating pressure recommended.

For detailed Engineering & Specification data, IOM and CAD Drawings, visit the Model Page on the BERMAD website.

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.
© Copyright 2016-2026 BERMAD CS Ltd