BURST CONTROL VALVE, EXCESSIVE FLOW

with Mechanical Flow Stem

Model 790-M

Hydraulically operated, diaphragm actuated, burst control valve that senses flow levels. When it senses flow in excess of settings, it shuts off and locks drip tight until manually reset. As long as flow is lower than settings, the valve remains fully open, minimizing head loss. A flow stem enables limiting valve opening stroke, precisely adjusting the required flow through the valve.

The BERMAD 700 SIGMA EN/ES series valves are hydraulic globe valves with a raised seat and double chamber actuator. They provide unobstructed flow, effective high-pressure modulation, and minimal cavitation, complying with various potable water standards.




Features & Benefits

- Certified to functional and drinking water standards: EN-1074, NSF-ANSI 61-372, WRAS, AS 5081 and others
- Designed to - Stand up to the toughest conditions
  - Excellent anti-cavitation properties
  - Wide flow range
  - High stability and accuracy
  - Drip tight sealing
- Double chamber design
  - Moderated valve reaction
  - Protected diaphragm
  - Optional operation in very low pressure
  - Moderated closing curve
- Flexible design - Easy addition of features
- Obstacle free flow pass
- V-Port throttling plug (optional) - Very stable at low flow
- High quality materials
- In-line serviceable - Easy maintenance


Typical Applications


- Old or sensitive pipe systems - Prevents flooding and water loss

Typical Installation




All images in this catalog are for illustration only





Closed



Open

This drawing refers to 1½ – 16"; 40-400 mm sized valves only. For other sizes please refer to the Model's IOM.

Main Valve

Size Range:
EN Series: 1½"-16"; DN40-400
ES Series: 2½"-24"; DN65-600
Pattern: "Y" (globe)
Pressure Rating: 16 bar; 25 bar
End Connection: Flanged
Plug Types: Flat disc, V-port, Cavitation cage
Temperature Rating: 80°C
For 60–80°C consult factory

Standard Materials:

Body & Cover: Ductile Iron
Bolts, Nuts & Studs: Stainless Steel
Internals: Stainless Steel, Tin Bronze, Coated Steel & POM
Diaphragm: Fabric-reinforced synthetic rubber
Seals: Synthetic rubber
Coating: Dark blue Fusion bonded epoxy
For other materials contact BERMAD

Pilot standard materials:

Body: Stainless Steel, Bronze & Brass
Elastomers: Synthetic Rubber
Internals and Spring: Stainless Steel

Pilot Options:

Various pilots and calibration springs are available.
Select according to valve size and operating conditions.
For more details check relevant pilots product pages.

Control System

Standard Materials:

Accessories: Stainless Steel, Bronze & Brass
Tubing: Stainless Steel or Copper
Fittings: Stainless Steel or Brass

Notes

- Burst flow settings should be at least 25% higher than the maximum allowed system flow.
- Inlet Pressure, Outlet Pressure and Flow-rate are required for optimal sizing.
- Recommended maximum flow velocity: 6.0 m/sec; 20 ft/sec.
- Minimum operating pressure: 0.7 bar; 10 psi. For lower pressure requirements consult factory.

For detailed Engineering & Specification data, IOM and CAD Drawings, visit the Model Page on the BERMAD website.

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.
© Copyright 2016-2026 BERMAD CS Ltd