PRESSURE SUSTAINING VALVE

with Solenoid Control

Model 730-55

Pressure relief/sustaining hydraulically operated control valve that can fulfill either of two separate functions: When installed in-line, it sustains minimum pre-set, upstream (back) pressure regardless of fluctuating flow or varying downstream pressure. When installed as a "branched from the line" circulation valve it relieves excessive line pressure when above maximum pre-set. The valve either regulates or shuts off in response to an electric signal.

The BERMAD 700 SIGMA EN/ES series valves are hydraulic globe valves with a raised seat and double chamber actuator. They provide unobstructed flow, effective high-pressure modulation, and minimal cavitation, complying with various potable water standards.




Features & Benefits

- Certified to functional and drinking water standards: EN-1074, NSF-ANSI 61-372, WRAS, AS 5081 and others
- Designed to - Stand up to the toughest conditions
  - Excellent anti-cavitation properties
  - Wide flow range
  - High stability and accuracy
  - Drip tight sealing
- Double chamber design
  - Moderated valve reaction
  - Protected diaphragm
  - Optional operation in very low pressure
  - Moderated closing curve
- Flexible design - Easy addition of features
- Obstacle free flow pass
- V-Port throttling plug (optional) - Very stable at low flow
- High quality materials
- In-line serviceable - Easy maintenance


Typical Applications


- Water delivery system - Prioritizing upstream over downstream demand
- Water delivery system - Prioritizing upstream demand to maintain pressure
- Pumping stations - Ensure operating point on pump curve
- Pumping stations - Circulation during low demand
- Filtration system - Sustaining minimum pressure for efficient backflush

Typical Installation




All images in this catalog are for illustration only





Closed



Regulating

This drawing refers to 1½ – 8"; 40-200 mm sized valves only. For other sizes please refer to the Model's IOM.

Main Valve

Size Range:
EN Series: 1½"-16"; DN40-400
ES Series: 2½"-24"; DN65-600
Pattern: "Y" (globe)
Pressure Rating: 16 bar; 25 bar
End Connection: Flanged
Plug Types: Flat disc, V-port, Cavitation cage
Temperature Rating: 80°C
For 60–80°C consult factory

Standard Materials:

Body & Cover: Ductile Iron
Bolts, Nuts & Studs: Stainless Steel
Internals: Stainless Steel, Tin Bronze, Coated Steel & POM
Diaphragm: Fabric-reinforced synthetic rubber
Seals: Synthetic rubber
Coating: Dark blue Fusion bonded epoxy
For other materials contact BERMAD

Control System

Standard Materials:

Accessories: Stainless Steel, Bronze & Brass
Tubing: Stainless Steel or Copper
Fittings: Stainless Steel or Brass

Pilot standard materials:

Body: Stainless Steel, Bronze & Brass
Elastomers: Synthetic Rubber
Internals and Spring: Stainless Steel

Pilot Options:

Various pilots and calibration springs are available.
Select according to valve size and operating conditions.
For more details check relevant pilots product pages.

Solenoid standard materials:

Body: Brass or Stainless Steel
Elastomers: NBR or FPM
Enclosure: Molded Epoxy

Solenoid Electrical Data:

Voltages:
(AC): 24, 110-120, 220-240, (50-60Hz)
(DC): 12, 24, 110, 220
Power Consumption:
(AC): 30VA, inrush; 15VA (8W), holding or 70VA, inrush; 40VA (17.1W), holding
(DC): 8-11.6W
Values may vary according to specific solenoid model.
For more details check solenoid product page.

Notes

- Inlet Pressure, Outlet Pressure and Flow-rate are required for optimal sizing and cavitation analysis.
- Recommended continuous flow velocity: 0.1-6.0 m/sec; 0.3-20 ft/sec.
- Minimum operating pressure: 0.7 bar; 10 psi. For lower pressure requirements consult factory.

For detailed Engineering & Specification data, IOM and CAD Drawings, visit the Model Page on the BERMAD website.

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.
© Copyright 2016-2026 BERMAD CS Ltd