


93400 **93401** 93410 93411

93401 | Messing | Hebelgriff | IG/AG
93401 | Brass | Lever handle | F/M



Druck-Temperatur-Diagramm pressure-temperature-diagram



Konstruktionsmerkmale Kugelhahn
- Schwimmende Kugel
- Griffstellung gibt die Durchflussrichtung an
- Wartungsfrei
- Ausblassichere Schaltwelle
- Gewinde nach DIN ISO 228-1
- Gehäuse aus Messing sandgestrahlt vernickelt

Standardtemperaturbereich
- 20°C bis + 90°C (abhängig vom Betriebsdruck)
Siehe Druck-Temperaturdiagramm

Zulassungstext
Einstufung nach PED Kategorie 0 PED 2014-68-EU, LABS konform nach VDMA 24364

Verwendung
Druckluft, Wasser allgemein, Kraftstoffe, Heizungskreisläufe, Heizöl, Öl, Thermoöl, Tyfocor

Design features ball valve
- Floating ball
- Handle position indicates flow direction
- Maintenance-free
- Blow out proved stem design
- Thread acc. to DIN ISO 228-1
- Brass body sand blasted and nickel plated

Standard temperature range
- 20°C to + 90°C (depending on working pressure)
Take a look at the pressure-temperature-diagram

Approval text
Classification acc. to PED category 0 PED 2014-68-EU, LABS conformity acc. to VDMA 24364


Suitable for
Compressed air, general water, Fuels, Heating circuits, Heating oil, Oils, Thermo-oil, Tyfocor

BESTELLBEISPIEL: Kugelhahn Innengewinde/Außengewinde mit Hebelgriff Größe 1/2" = 93401-1/2" Artikel-Nr. 0020041052015
ORDERING EXAMPLE: Ball valve female/male thread with lever handle size 1/2" = 93401-1/2" item number 0020041052015

Datentabelle data table

D1	D2	DN (mm)	LW (mm)	PN (bar)	L (mm)	L1 (mm)	L2 (mm)	MM (mm)	R (mm)	H (mm)	D (mm)	SW (mm)	Gewicht Weight (kg)	Artikel-Nr. Item number
G 1/4"	G 1/4"	8	8	12	41,5	10	9,5	21,5	72	31	24,5	21	0,098	0020041052006
G 3/8"	G 3/8"	10	8	12	41,5	10,5	9,5	21,5	72	31	24,5	21	0,096	0020041052010
G 1/2"	G 1/2"	15	10	12	49	12,5	13	26	72	33	29	25	0,136	0020041052015

Maßskizze measured sketch



Materialtabelle materials grid

Nr. No.	Bezeichnung Description	Werkstoff Material	Materialbezeichnung Material description
1	Gehäuse Body	Messing vernickelt Brass (nickel-plated)	CW617N
2	Kugel Ball	Messing verchromt Brass (chrome-plated)	CW617N
3	Kugeldichtung Ball seal	PTFE PTFE	-
4	Flansch / Nippel Flange / nipple	Messing vernickelt Brass (nickel-plated)	CW617N
5	Schaltwelle Stem	Messing Brass	CW617N
7	Spindeldichtung Spindle seal	FKM FKM	-
8	Griff Handle	Polyamid Polyamide	-

Verpackungseinheiten Packing units

DN (mm)		
8	18	1
10	18	1
15	12	1