sferaco
VALVES, METERS & FITTINGS

ISO 9001 : 2015
BUREAU VERITAS
Certification

REF. 7151

2 PIECES STAINLESS STEEL BALL VALVE PN63 INITIAL RANGE BSP

2 pieces stainless steel ball valve with full bore for Chemical industries, petrochemical industries, hydraulic installation, heating, water distribution, compressed air.
PTFE packing and PTFE filled with 15% Glass fiber seat.

Certificate 3.1

CE

LRQA
PED/2014/68/UE



Size :	DN1/4" to DN4"
Connection :	Female BSP
Min Temperature :	-20°C
Max Temperature :	+180°C
Max Pressure :	63 Bars (jusqu'au DN3/4")
Specifications :	Locking device Full bore Anti blow-out stem
Materials :	Stainless steel ASTM A351 CF8M

2 PIECES STAINLESS STEEL BALL VALVE PN63 INITIAL RANGE BSP


SPECIFICATIONS :

- Full bore
- Anti blow-out stem
- PTFE packing
- PTFE filled with 15% Glass fiber seat
- Locking device
- Solid ball up to DN1"1/2, hollow ball over
- 2 pieces type

USE :

- Chemical and pharmaceutical industries, petrochemical industries, hydraulic installation, compressed air
- Min and max Temperature Ts : -20°C to + 180°C
- Max Pressure Ps : 63 bars up to DN3/4",50 bars from 1" to 1"1/4,40 bars from 1"1/2 to 2" , 25 bars from 2"1/2 to 3", 16 bars for DN4" (see graph)

PRESSURE / TEMPERATURE GRAPH (STEAM EXCLUDED) :



Information provided as an indication and subject to possible modification

2 PIECES STAINLESS STEEL BALL VALVE PN63 INITIAL RANGE BSP

TORQUE VALUES (in Nm without safety coefficient) :

DN	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
Torque (Nm)	5		7	13	18	25	35	40	60	70	100

RANGE :




- Ball valve female / female threaded BSP Stainless steel blue handle Initial range **Ref. 7151** from DN1/4" to DN4"


2 PIECES STAINLESS STEEL BALL VALVE PN63 INITIAL RANGE BSP

MATERIALS :

DN1/4" - 1"1/2



DN2" - 4"




Item	Designation	Materials
1	Body	ASTM A351 CF8M
2	Seat	PTFE filled with 15% glass fiber
3	Ball	AISI 316
4	Body seal	PTFE
5	Ends	ASTM A351 CF8M
6	Thrust washer	PTFE
7	Gland ring	AISI 304
8	Spring washer	
9	Stem	AISI 316
10	Nut	AISI 304
11	Handle	
12	Handle cover	PVC
13	Packing	PTFE
14	Locking device	AISI 304


Information provided as an indication and subject to possible modification

2 PIECES STAINLESS STEEL BALL VALVE PN63 INITIAL RANGE BSP

SIZE (in mm) :



Stem size :



DN	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
Ø P	11.5	12.5	15	20	25	32	38	50	65	76	94
L	40	41	50	56	68	83	90	111	146.5	168	213
E	85		95	120		135	170		235		335
H	44	44	46	53	57	71	75	96	128	135	160
L1	8	9.5	11.5	12	15	16.5	17	20	29	32	37
W (on flat)	16.5	20	24	30	36.5	46	53	65.5	83	96	122
C	5			5.8		7		8	12		14
Ø Y	M8					M10		M12	M16		M20
Weight (Kg)	0.14	0.15	0.22	0.31	0.44	0.8	1.1	1.67	3.48	4.7	9.1
Ref.	715102	715103	715104	715105	715106	715107	715108	715109	715110	715111	715112

Information provided as an indication and subject to possible modification

2 PIECES STAINLESS STEEL BALL VALVE PN63 INITIAL RANGE BSP

STANDARDS :

- Manufacturer certified ISO 9001 : 2015
- DIRECTIVE 2014/68/EU: For liquids or Gas of Group 1
    - DN1/4"-1": Article 4, §3 (SEP), no CE marking
    - DN1"1/4-4": Risk category II, CE 0343 marking
- Certificate 3.1 on request
- Pressure Tests according to EN 12266-1, rate A
- Female BSPP internal parallel thread according to ISO 228-1

ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.
The customer must check the right choice of the products with the real service conditions.