Vexve underground ball valve

Series 157/SL/HG, welding / welding, EN (DIN), full bore, DN 150-300, PN 25

DN 150-300

Materials

Body	DN 150-300: Steel, P235GH (1.0345)
Ball	DN 150-300: Stainless steel, X5CrNi18-10 (1.4301)
Ball seal	DN 150-300: PTFE+C
Stem	DN 150-300: Stainless steel, X8CrNiS18-9 (1.4305)
Stem seal	DN 150-300: FPM
Top of Stem	DN 150-300: Stainless steel, X5CrNi18-10 (1.4301)

Mounting

welding / welding, EN (DIN)

Operation

DN 150-300	valves are available with angle gear standard hexagon adapter 27 or 32 mm

Operating conditions

Temperature	-20 °C - +200 °C
Leakage rate	A (EN 12266-1)

Below -20 °C contact manufacturer. Lowest allowed ambient temperature -40 °C.

DN 150-300

water area

Steam area (not allowed)

short-term working area

Copyright © Vexve Oy - All rights reserved

Vexve underground ball valve

Series 157/SL/HG, welding / welding, EN (DIN), full bore, DN 150-300, PN 25

DN 150-300 **DN 150-300**

Dimensions

DN	PN	Product no.	D	D1	D2	D3	H1	H2	H3	H4	L	L1	L2	S1	S2	W1	W2	Kg
150	25	157150/SL/HG	150.0	168.3	273.0	76.1	490.0	406	334	713	1500	84.0	149	7.1	4.5	81	198	122
200	25	157200/SL/HG	200.0	219.1	355.6	88.9	525.0	415	327	764	1500	97.0	162	7.1	5.0	90	208	180
250	25	157250/SL/HG	250.0	273.0	457.0	101.6	580.0	443	331	809	1500	138.0	222	8.8	5.0	141	235	250
300	25	157300/SE/HG	290.0	323.9	508.0	114.3	603.0	440	329	832	1800	138.0	222	8.8	5.6	141	235	299

Other stem heights also available

Copyright © Vexve Oy - All rights reserved