Vexve gas ball valve

Series 112, female threads / female threads, reduced bore, DN 15-50, PN 40



DN 15-50

Materials

Body	DN 15-50: Steel, P235GH (1.0345)
Ball	DN 15-50: Stainless steel, X5CrNi18-10 (1.4301)
Ball seal	DN 15-50: PTFE+C
Stem	DN 15-50: Stainless steel, X8CrNiS18-9 (1.4305)
Stem seal	DN 15-50: FPM/NBR

Mounting

female threads / female threads


Operation

DN 15-50	composite handle

Operating conditions

Temperature	-40 °C - +70 °C
Leakage rate	A (EN 12266-1)

Below -30 °C contact manufacturer. Lowest allowed ambient temperature -40 °C.




DN 15-50

Copyright © Vexve Oy - All rights reserved

Vexve gas ball valve

Series 112, female threads / female threads, reduced bore, DN 15-50, PN 40



DN 15-50

Dimensions

DN	PN	Product no.	A	D	D1	D2	D3	H	H1	L	Kg
15	40	112015X	130.0	10.0	Rp 1/2	33.7	32	119	84.0	85	0.4
20	40	112020X	130.0	15.0	Rp 3/4	42.4	32	123	81.0	100	0.6
25	40	112025X	130.0	20.0	Rp 1	48.3	32	125	84.0	115	0.7
32	40	112032X	130.0	25.0	Rp 1 1/4	60.3	32	129	83.0	130	1.1
40	40	112040X	130.0	32.0	Rp 1 1/2	70.0	32	133	84.0	205	1.4
50	40	112050X	130.0	40.0	Rp 2	76.1	32	140	85.0	205	2.0

Copyright © Vexve Oy - All rights reserved